



HS-GH-3-12-A

Grundhalter
Basic holder
Support de base



di-soric GmbH & Co. KG
Steinbeisstraße 6
DE-73660 Urbach
Germany
Tel: +49 (0) 7181/9879-0
info@di-soric.com · www.di-soric.com




Technische Daten	Technical data	Caractéristiques techniques	+20°C
Produktserie	Product series	Gamme de produits	Z-UBT-KL-MS Montagesystem / Z-UBT-KL-MS Assembly system / Système de montage Z-UBT-KL-MS
Durchm. Montagezapfen/Bohrung	Diameter Mounting pin / boring	Diam. tourillon de montage/alésage	Ø 12 mm
Material	Material	Matériau	Aluminium / Aluminum / Aluminium

Stand 03.11.23, Änderungen vorbehalten
As of 11/03/23, subject to change
État 03.11.23, sous réserve de modifications


HS-GH-3-12-A

基本支座



di-soric GmbH & Co. KG
Steinbeisstraße 6
DE-73660 Urbach
Germany
Tel: +49 (0) 7181/9879-0
info@di-soric.com · www.di-soric.com

210009



mm

技术数据

+20°C

产品系列

Z-UBT-KL-MS 安装系统

直径装配栓/钻孔


Ø 12 mm

材料


铝

版本 23.11.03, 保留变更权

Grundhalter Ø 12 mm




Basic system holder Ø 12 mm




12 mm du support Ø de système de base

Grundhalter Ø 15 mm



Basic system holder Ø 15 mm



15mm du support Ø de système de base