





## 213332 IOL-Portable IOL Portable

- Universal IO-Link handheld master
- App-based, no prior knowledge necessary
- Integrated touchscreen and plug connectors
- Integrated battery, IO-Link master and WLAN
- For identification, configuration and diagnostics
- IODD download via IODDfinder
- For devices with IODD Specification 1.1



Function													
													
<div> <div>CE</div> <div>UKCA</div> <div></div> </div>													
Technical data (typ.)							+20°C, 24 V DC						
Power consumption							80 mA						
Inverse polarity protection							Yes						
Power supply							24V / 80 mA (IO-Link Device from battery)						
Housing dimensions							62 x 222 x 90 mm						
Housing material							Polycarbonate						
Protection class							III, operation on protective low voltage						
To be used for							For devices with IODD Specification 1.1						
Scope of delivery							IO-Link Hand Held Master, cable with clamps 0,3 m with connector M12, 4-wires, Protection bag, Micro-USB-cable, Quick-start-guide						
Functions							Without computer						
Communication							IO-Link specification V 1.1, IO-Link port class A						
Ambient temperature during operation							0 ... +40 °C						
Protection type							IP 30						
Connection							Socket, M8, 3-pin						
Connection 2							Socket, M8, 4-pin						
Connection 3							Socket, M12, 4-pin						
More information / accessories							<a href="https://www.di-soric.com/213332">https://www.di-soric.com/213332</a>						