




HS-S-15-200-A

Montagestange
Mounting rod
Tige de montage



di-soric GmbH & Co. KG
Steinbeisstraße 6
DE-73660 Urbach
Germany
Tel: +49 (0) 7181/9879-0
info@di-soric.com · www.di-soric.com



Technische Daten	Technical data	Caractéristiques techniques	+20°C
Produktserie	Product series	Gamme de produits	Z-UBT-KL-MS Montagesystem / Z-UBT-KL-MS Assembly system / Système de montage Z-UBT-KL-MS
Durchm. Montagezapfen/Bohrung	Diameter Mounting pin / boring	Diam. tourillon de montage/alésage	Ø 15 mm
Maß B	Dimension B	Dimension B	200 mm
Material	Material	Matériau	Aluminium / Aluminum / Aluminium

Stand 03.11.23, Änderungen vorbehalten
As of 11/03/23, subject to change
État 03.11.23, sous réserve de modifications




HS-S-15-200-A

装配杆




di-soric GmbH & Co. KG
Steinbeisstraße 6
DE-73660 Urbach
Germany
Tel: +49 (0) 7181/9879-0
info@di-soric.com · www.di-soric.com




技术数据		+20°C
产品系列	Z-UBT-KL-MS 安装系统	
直径装配栓/钻孔	Ø 15 mm	
尺寸 B	200 mm	
材料	铝	

版本 23.11.03，保留变更权

Grundhalter Ø 12 mm



Basic system holder Ø 12 mm



12 mm du support Ø de système de base

Grundhalter Ø 15 mm

