





204163

OEP 12 V 20000 G2L-5M

High performance light barrier, receiver

- Range up to 20 m
- Integrated amplifier electronics
- Transistor output with push-pull
- High function reserve
- Extremely dirt-resistant
- Easy adjustment
- Different designs to be combined
- High protection type
- Compact design



1) LED

BK: black

BN: brown

BU: blue

Function



Technical data (typ.)

+20°C, 24 V DC

Service voltage	10 ... 35 V DC
No-load current (max.)	40 mA
Thread	M12 x 1
Housing length	60 mm
Housing material	Stainless steel (V2A 1.4301 / AISI 304)
Material of cable	PVC
Protection class	III, operation on protective low voltage
Operating principle	Through-beam sensor, receiver
Evaluation	digital
Design	Thread
Characteristics	High transmit power and dirt penetration
Consisting of	Receiver
Switching output	Push-pull, 200 mA, NO (pnp) / NC (nnp)
Ambient light immunity	15 kLx Sunlight, 2 kLx Clocked light
Range	0 ... 20000 mm (dependent on the transmitter)
Sensitivity adjustment	no setting elements
Switching frequency	150 Hz
Shock/vibration load	30 g, 11 ms / 10 ... 55 Hz, 2.0 mm
Ambient temperature during operation	-20 ... +60 °C
Protection type	IP 67 / IP 68 / IP 69K

**204163****OEP 12 V 20000 G2L-5M****High performance light barrier, receiver****Technical data (typ.)**

Connection

+20°C, 24 V DC

Cable, 5.0 m

More information / accessories<https://www.di-soric.com/204163>