




206805

BEK-F100/100-G3TI-IBS

Area light

- Constant level of light intensity over the entire voltage range
- Homogeneous luminous field
- High efficiency
- Light intensity can be adjusted



Function



Technical data (typ.)

+20°C, 24 V DC

Service voltage	18 ... 35 V DC (Supply Class 2)
No-load current (max.)	290 mA (24 V DC)
Power	7.0 W (24 V DC)
Inverse polarity protection	Yes
Illuminated area	100 x 100 mm
Housing dimensions	130 x 160 x 15 mm
Housing material	Aluminum (Black, Anodized)
Material	PC, opal diffuse (Protection optics)
Protection class	III, operation on protective low voltage
Risk group (DIN EN 62471)	Free group
Design	Area light
Characteristics	Trigger input
Trigger input high level	3.3 ... 35.0 V
Trigger input low level	< 2.8 V
Light source	LED
Color	Blue
Wavelength	469 nm
Deflection angle FWHM	120°
Control	Integrated power control
Display	LED Green - Operating display
Shock/vibration load	30 g, 11 ms / 10 ... 55 Hz, 1.0 mm
Ambient temperature during operation	0 ... +40 °C
Protection type	IP 67



206805
BEK-F100/100-G3TI-IBS
Area light

Technical data (typ.)

Connection

Connection cable

+20°C, 24 V DC

Connector, M12, 3-pin

VK ...

More information / accessories<https://www.di-soric.com/206805>