


Ringlight

- 



A utiliser exclusivement
avec un contrôleur
d'impulsion connecté a
une alimentation *Class 2*!

Function



+20°C, 24 V DC

230 W
8
12000 mA
No constant voltage!
Yes
500 V
Ø 131 / Ø 200 mm (Diameter)
20 mm
Aluminum (Black, Anodized)
■ Polyurethane (Cable)
■ PMMA, diffuse (Protection optics)
Free group
Ringlight
LED
red (diffuse)
633 nm
30°



207152
BE-R130-F1-K-DIF
Ringlight

Technical data (typ.)

Light intensity

+20°C, 24 V DC

- 2.30 kLx (300.0 mm / 100 %)
- 9.20 kLx (300.0 mm / 400 %)
- 17.2 kLx (300.0 mm / 800 %)
- 1.00 kLx (500.0 mm / 100 %)
- 4.00 kLx (500.0 mm / 400 %)
- 7.40 kLx (500.0 mm / 800 %)

Control

Flashable by means of flash controller

Shock/vibration load

30 g, 11 ms / 10 ... 55 Hz, 1.0 mm

Ambient temperature during operation

0 ... +40 °C

Protection type

IP 67

Connection

Cable, 2.5 m (flying leads, Use only with flash controller!)

More information / accessories

<https://www.di-soric.com/207152>