





207304

LA-D 56-12.5-688-860 I-H

Light grids

- Diagonal beam evaluation
- Integrated evaluation electronics
- Switching output
- Fault alarm output
- Compact design
- Aluminum housing
- Easy to install



- 1) Transmitter
2) Receiver
3) Monitoring height H
4) Profile length L
5) Synchronous beam
6) Profile cross section

Function



Technical data (typ.)

+20°C, 24 V DC

Service voltage	20.4 ... 28.8 V DC
Power consumption	8 W
Assembly	Threaded bolt (2)
Profile cross section	12 x 24 mm
Dimension	■ A: 80 mm ■ B: 700 mm ■ X: 13.5 mm ■ Y: 153.5 mm
Profile length	860 mm
Housing material	Aluminum (silver, Anodized)
Protection class	III, operation on protective low voltage
EMC directives	EN 61000-6-3:2001 / EN 61000-6-1:2001
Evaluation	diagonal
Evaluation electronics	integrated
Output function	Light switching
Switching output	pnp, 200 mA, NC, short-circuit-proof
Light source	LED
Color	Infrared
Wavelength	880 nm

**207304****LA-D 56-12.5-688-860 I-H****Light grids****Technical data (typ.)****+20°C, 24 V DC**

Beam evaluation	via integrated evaluation electronics
Beam separation	12.5 mm
Number of beams	56
Monitoring height	688 mm
Range	700 ... 4000 mm (factory setting)
Display	LED (Service voltage / output stage, error (alarm))
Cycle time per light beam	1 ms
Total cycle time	Anzahl Lichtstrahlen x 1 ms + 4 ms
Basic processing time	4 ms
Ambient temperature during operation	-10 ... +45 °C
Protection type	IP 54 (IP 65 optional)
Connection	Cable, 4.0 m (with ferrule)

More information / accessories**<https://www.di-soric.com/207304>**